

EN 50155 Routing Switch

Viper-212



- ⌘ Compact rail-approved Ethernet switch solution
 - Single model 24 – 110VDC power range
 - 12 x 100 Mbit/s Ethernet ports
 - WeOS – Layer 3 switch and router functions
- ⌘ Externally tested and verified to EN50155
 - Surge resistance and isolation
 - Magnetic field immunity & conducted emission
 - Shock and vibration
- ⌘ Designed for long life and extreme operational environments
 - IP65 anti-condensation Gore-Tex® membrane
 - Ambient temperature –40°C (–40°F) to +70°C (+158°F)
 - Integrated M12 threading & high MTBF, 554,000 hours
- ⌘ Design and production testing to match requirements for train control
 - Post production testing exceeding EN 50155 mandatory requirement
 - Burn in and isolation test on all units
 - Manufactured according to IPC-A-610D class2



EN 61000-6-2
Industrial Immunity

EN 61000-6-4
Industrial environments

EN 50155
On Board Rail

EN 50121-4
Railway Trackside

The Viper-212 is a managed 12 port routing switch designed to meet the full requirements of the rail vehicle market. The incredibly compact and robust housing ensures the unit can be built into tight and environmentally hostile spaces. The Westermo WeOS operating system provides an extensive suite of IP networking standards allowing resilient and flexible networks to be created, meeting the needs of the rail market.

As is critical for all equipment to be installed in rail vehicles, the Viper has been externally tested across the complete spectrum of standards required by EN50155.

Westermo understand that systems on railcars are required by the EN50155 standard to have a useful life of 20 years, so as well as using the highest quality components to deliver extended MTBF figures, we also implement features like the Gore-Tex® membrane in the IP65 enclosure to prevent water build up in the units. Due to the high vibration environment of the rail industry, we have also developed the Viper case with integral threading for the M12 connectors to ensure the IP65 seal is maintained for the life of the product.


The EN50155 standard requires mandatory performance and isolation testing. Not only does Westermo meet these, we exceed them in order to meet the additional manufacturer requirements for train control. Westermo's Swedish factory has been building Ethernet switches for the railcar market for many years now and understands the measures that are required to provide the highest quality manufactured solutions.

Ordering Information

Art.no	Description
3641-0560	Managed EN 50155 switch with routing functionality –Viper-212

Specifications Managed EN 50155 switch with routing functionality –Viper 212

Dimensional drawing



Weight 1.4 kg
Degree of protection IP 65

Power	
Operating voltage	Rated: 24 to 110 VDC Operating: 24 to 110 VDC ± 30 % Operating for 100 ms: 24 to 110 VDC ±40%
Rated current	350 mA @ 24 V and 150 mA @ 110 V

Interfaces	
X1 – X12, Ethernet ports	12 × 10/100 Mbit/s
USB	1 × USB 2.0 host interface
CON	1 × RS-232, 115.2 kbit/s

Temperature	
Operating	–40 to +70°C (–40 to +158°F)
Storage & Transport	–50 to +85°C (–58 to +185°F)

Agency approvals and standards compliance	
EMC	EN 61000-6-1, Immunity residential environments
	EN 61000-6-2, Immunity industrial environments
	EN61000-6-3, Emission standard for residential, commercial and light-industrial environments
	EN 61000-6-4, Emission industrial environments
	EN 55022 +A1, Emission IT equipment
	EN 55024, Immunity IT equipment
	FCC part 15 Class B
	EN 50121-4, Railway signaling and telecommunications apparatus
	EN 50121-3-2:2006 Railway applications –Rolling stock – apparatus
	EN 50155:2007 Railway applications – Electronic equipment used on rolling stock
IE C 62236-4, Railway signaling and telecommunications apparatus	
Safety	EN 60950-1, IT equipment
Environmental	EN 61373:1999 – Railway applications – Rolling stock equipment. Shock and vibration tests
	IEE 1478:2001 – Environmental conditions for transit rail car electronic equipment
	EN 50124-1: 2001+A1:2003+A2:2005 – Railway applications – Insulation coordination
	Fire safety standard CEN 45545-2